

WOLF GAS & ELECTRIC CONVECTION OVENS

Quality Construction for Lasting Performance and Easy Care.

Wolf Convection Ovens' attractive designs bring an appealing look to your work area. Even heat distribution provides consistent results when baking, roasting or rethermalizing.

Standard Features:

- Stainless steel front, sides and top
- Stainless steel doors with double pane windows
- 2 HP two-speed oven blower motors; 115/60/1 with 6 ft. cord and plug
- Oven cool switch for rapid cool down
- Porcelain enamel on steel oven interior
- Five nickel-plated oven racks with eleven rack positions
- Interior oven light



WKGD-2



WKGD-1

WK SERIES GAS CONVECTION OVENS

Standard Features:

- 44,000 BTU/hr burner per oven section
- 3/4" rear gas connection
- Electronic spark ignition
- Internal combination gas pressure regulator and safety solenoid system

Model Number	Description	Approx. Shipping Wt.	
		lbs	kg
WKGD-1	Single deck on 25 3/4" legs	497	225
WKGD-2	Double deck on 8" legs	994	450

*Caster prices for double deck ovens include a deduction for legs.

Freight Classification: 85

WKG Series – Full Size Model #	# of Sections	Exterior Dimensions W x D x H	Oven Cavity Dimensions W x D x H	Total BTU/hr	Motor Size
WKGD-1	1	40" x 41 1/2" x 56 3/4"	29" x 22 1/8" x 20"	44,000	(1) 1/2 HP, 115 V, 9 amp
WKGD-2	2	40" x 41 1/2" x 70"	29" x 22 1/8" x 20"	88,000	(2) 1/2 HP, 115 V, 9 amp

WK SERIES ELECTRIC CONVECTION OVENS

Standard Features:

- 12.5 kW input burner per oven section
- 208 V or 240 V, 60 Hz, 1 or 3 phase

Model Number	Description	Approx. Shipping Wt.	
		lbs	kg
WKED-1	Single deck on 25 3/4" legs	497	225
WKED-2	Double deck on 8" legs	994	450

*Caster prices for double deck ovens include a deduction for legs.

Freight Classification: 85

WKE Series – Full Size Model #	# of Sections	Exterior Dimensions W x D x H	Oven Cavity Dimensions W x D x H	Total kW	Standard Power Supply
WKED-1	1	40" x 41 1/2" x 56 3/4"	29" x 22 1/8" x 20"	12.5	208/240 V, 60 Hz, 1 or 3 phase
WKED-2	2	40" x 41 1/2" x 70"	29" x 22 1/8" x 20"	25	208/240 V, 60 Hz, 1 or 3 phase

OPTIONS & ACCESSORIES FOR WK CONVECTION OVENS

Option
5-hour timer in place of 60-minute timer—D control models
Roast & hold (per section)—D control gas models
Simultaneous doors (per section)—chain driven
480 V, 60 Hz, 3 phase (per section)—VC electric models

Accessory	Accessory Code
One rack	WKGRACK 1PC
Rack hanger	RACK HANGRW
3/4" x 4 ft. quick disconnect hose	3/4 QDH 4FT
Stainless steel drip pan	DRIPPAN SSTWKG
Down draft diverter	DWNRFT DIVWKG
Stainless steel leg stand with adjustable feet, stainless steel shelf and adjustable rack supports	WKGOPEN STDLEG
Stainless steel leg stand with casters, stainless steel shelf and adjustable rack supports	WKGOPEN STDCST